Applicant(s): Jung-Lim Yoon, et al. U.S. Serial No.: Not yet assigned

REMARKS

The amendments to the specification are made to clarify the description. No new matter is added to the application.

Attached hereto is a marked-up version of the changes made to the application by the current Amendment. The attached page is captioned "Version with Markings to Show Changes Made."

Date: 10/10/01

MILLS & ONELLO, LLP

Eleven Beacon Street, Suite 605

Boston, MA 02108

Telephone: (617) 994-4900, Ext. 4901

Facsimile: (617) 742-7774

J:\SAM\0260\prelimamend.wpd

Respectfully submitted,

Steven M. Mills

Registration Number 36,610 Attorney for Applicants Applicant(s): Jung-Lim Yoon, et al. U.S. Serial No.: Not yet assigned

Version with Markings to Show Changes Made

In the Specification

The specification has been amended as follows:

The paragraph at page 6 line 22 through page 7 line 10 has been amended as follows:

(Amended) In the passivation layer 60 of the pad area, at least one <u>first</u> [fist] metal line 68a is disposed, and in the passivation layer 60 of the fuse area b, a plurality of, for example at least a pair of, second metal lines 68b are disposed. Top surfaces of the first and second metal lines 68a, 68b have the same height as a top surface of the passivation layer 60. The first and second metal lines 68a, 68b include a copper layer pattern 67 having superior conductivity and electromigration as compared with an aluminum layer, and a diffusion barrier metal layer pattern 65 enclosing side walls and bottoms of the copper layer pattern 67. It is desirable that the diffusion barrier metal layer pattern 65 include a material layer, for example a tantalum nitride layer which can prevent copper elements in the copper layer pattern 67 from penetrating through the interlayer insulation layer 53 and the passivation layer 60.